

MODEL I08-2000

Machine for:

- impregnation
- Inks reactivation

1. HEATING CYLINDER'S CHARACTERISTICS:

- 1.1. Diameter: 800 mm (31,49").
- 1.2. Width: 2.000 mm (78,74").
- 1.3. Working width: 1.800 mm (70,87").

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A system.
- 2.2. The temperature of the cylinder is regulated by a touch screen and is regulated by an electronic card. The temperature control is equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

- 3.1. Tension control for material to be treated:
 - Entry: axial unwinding with disk brake with pneumatic adjustment and fabric manual brake
 - Exit: independent double-roller tangential winding, possibility of «soft» or «hard» winding by transmission management, potentiometer control

4. OTHER DEVICES INTO MACHINE:

- 4.1. Independent motors with an electronic synchronization system
- 4.2. Meter-counter, with alarm to predetermine the length of production runs
- 4.3. General management of the machine, including temperature control by adjustable PLC for the memorization of production data
- 4.4. Removable and interchangeable AISI 304 tank for impregnation liquid
- 4.5. Recirculation system of the impregnating liquid
- 4.6. Squeezer with rubberized rollers, one of which is stationary motorized and one is idle and controlled by pneumatic pistons
- 4.7. Fumes hood with condensate separation
- 4.8. Front touch-screen keyboard for production data access and programming

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 400 mm (15,75").
- Fabric roll diameter in exit 400 mm (15,75").

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL I08-2000

6. TECHNICAL DATA:

- 6.1. Installed power: 54,15 kW.
- 6.2. Average electric consumption: 36,30 kWh.
- 6.3. Power in ECONOMY MODE: 37,15 kW.
- 6.4. Compressed air pressure: 6-8 bar.
- 6.5. Mechanic speed: 0.4 ÷ 8 mt/min.
- 6.6. Overall dimensions: width 3.860 mm (151,97"). Length with tank inserted 2.185 mm (86,02"). Length with tank extracted 2.735 mm (107,68"). Height 2.640 mm (103,94").
- 6.7. Net weight: 4.950 Kg.
- 6.8. Machine produced according to CE rules.
- 6.9. Customs tariff: 84 51 80 80.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

INNOVATION
SPEED
FLEXIBILITY
PROJECT&DESIGN
INSTALLATION AND ASSISTANCE



Monti Antonio S.p.A.
Head Office: via dell'Elettronica n°5, 36016 Thiene (VI) Italy
Operation and Administration: viale della Fisica n°6, 36016 Thiene (VI) Italy
T. +39 0445 364619 - F. +39 0445 364033
sales@montiantonio.com - www.montiantonio.com