

MODEL 104E

Sucking and steaming double press for knitwears ironing/finishing, with upper electric plate

1. MACHINE CHARACTERISTICS
 - 1.1. Planes number: 2 sucking and steaming
 - 1.2. Oscillating/parallel upper plane, electrically heated and with adjustable pressure
 - 1.3. Plane dimensions: 1.800 mm (70,87") x 920 mm (36,22").
2. HEATING AND TEMPERATURE CONTROL
 - 2.1. The oscillating/parallel upper plate is heated by means electric resistors controlled by electronic thermostat
 - 2.2. Every steaming plane is equipped with a self-heated steam chamber (lower plane) which guarantees dry steam
3. OTHER DEVICES INTO MACHINE
 - 3.1. Automatic, semi-automatic or manual functioning
 - 3.2. Microprocessor which memorizes all different working process
 - 3.3. Built-in powerful suction fan
 - 3.4. Only supplied without boiler but with steam inlet connections for external boiler
4. TECHNICAL DATA
 - 4.1. Installed power: 5,5 kW
 - 4.2. Average electric consumption: 4,5 kW/h
 - 4.3. Compressed air pressure: 6-8 bar
 - 4.4. Maximum and optimal steam feeding pressure: 3.5 bar
 - 4.5. Overall dimensions: width 3.950 mm (155,51"). length 1.600 mm (62,99"). height 2.300 mm (90,55").
 - 4.6. Net weight: 1.250 kg
 - 4.7. Machine produced according to CE rules
 - 4.8. Customs tariff: 84 51 30 00

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options