

MODEL 950 - 2600



Calender used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting – heatsetting
- Heatsetting of “crush” effect

1. CHARACTERISTICS OF PRINTING CYLINDER:

- 1.1. Diameter : 1.500 mm (59,05”).
- 1.2. Width : 2.600 mm (102,36”).
- 1.3. Working width: 2.400 mm (94,48”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by three resistors (heating elements) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. The temperature of the cylinder is set by a touch screen and is regulated by an electronic. The temperature control is equipped with an alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS

3.1. Tension control for printing material:

- Entry: disk brake with pneumatic adjustment and fabric manual brake
- Exit: independent motor, adjustable by potentiometer

3.2. Tension control for printing paper:

- Entry: disk brake with pneumatic adjustment.
- Exit: independent motor, adjustable with tension control by touch screen

3.3. Tension control for protection paper:

- Entry: disk brake with automatic adjustment
- Exit: independent motor, adjustable by potentiometer

4. OTHER DEVICES INTO MACHINE

- 4.1. Independent motors with a electronic synchronization system
- 4.2. NOMEX felt with tension adjustment system and automatic felt-centering device
- 4.3. Incorporated system for felt protection in case of black out and/or compressed air lack
- 4.4. Multifunctional electronic meter-counter, with alarm to predetermine the length of production runs
- 4.5. Temperature cooling system for printed fabric exit, complete with fan
- 4.6. Front touch-screen keyboard for production data access and programming

All data and technical features are purely indicative and subjected to changes without prior notice.



INNOVATION
SPEED
FLEXIBILITY
PROJECT&DESIGN
INSTALLATION AND ASSISTANCE

Monti Antonio S.p.A.
Head Office: via dell'Elettronica n°5, 36016 Thiene (VI) Italy
Operation and Administration: viale della Fisica n°6, 36016 Thiene (VI) Italy
T. +39 0445 364619 – F. +39 0445 364033
sales@montiantonio.com – www.montiantonio.com

MODEL 950 - 2600



5. TECHNICAL DATA

“POWER” modality

Installed power: 133 kw/h (42+42+42)

Average electric consumption: 87 kw/h

“ECONOMY” modality (42+42)

Installed power: 92 kw/h

Average electric consumption: 60 kw/h

5.1. Compressed air pressure: 6-8 bar

5.2. Mechanic speed: 1.5 - 30 m/min

5.3. Overall dimensions (with platform): width 4.190 mm (164,96”). length 4.200 mm (165,35”). height 2.325 mm (91,53”).

5.4. Net weight : 13.650 Kg

5.5. Machine produced according to EC rules

5.6. Customs tariff: 84 51 80 30

All data and technical features are purely indicative and subjected to changes without prior notice.



INNOVATION
SPEED
FLEXIBILITY
PROJECT&DESIGN
INSTALLATION AND ASSISTANCE

Monti Antonio S.p.A.
Head Office: via dell'Elettronica n°5, 36016 Thiene (VI) Italy
Operation and Administration: viale della Fisica n°6, 36016 Thiene (VI) Italy
T. +39 0445 364619 – F. +39 0445 364033
sales@montiantonio.com – www.montiantonio.com