

MODEL RP02-1800

Calender adapt for fabrics in continuous or in pieces (option):

- Transfer printing with pigment papers.
- Direct inks reactivation.
- Thermosetting – “crush” effect.
- Sublimation printing (option).

Polyvalent and versatile it is studied for pigment printing in the following working conditions:

- Paper in roll and material to be printed in roll.

1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter: 200 mm (7,87”).
- 1.2. Width: 1.800 mm (70,87”).
- 1.3. Working width: 1.650 mm (64,96”).

2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.A. system.
- 2.2. The temperature of the cylinder is set by touch screen and regulated by an electronic thermostat and equipped with temperature alarm system and a limitation system of maximum temperature (230 °C).

3. TENSION CONTROLS:

- 3.1. Tension control for printing material:
 - Entry: axial unwinding with disk brake with pneumatic adjustment.
 - Exit: motorized axial winding with pneumatic device for movement transmission of the main motor.
- 3.2. Tension control for printing paper:
 - Entry: axial unwinding with manual brake.
 - Exit: motorized axial winding with pneumatic device for movement transmission of the main motor.

4. OTHER DEVICES INTO MACHINE:

- 4.1. NOMEX felt with pneumatic tension adjustment system and felt-centring device by means of electromechanical sensor.
- 4.2. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.3. Meter-counter, with alarm to predetermine the length of production runs
- 4.4. General management of the machine, including temperature control by adjustable PLC for the memorization of production data
- 4.5. Front touch-screen keyboard for production data access and programming

5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 250 mm (9,84”).
- Fabric roll diameter in exit 250 mm (9,84”).
- Printing paper roll diameter in entry 250 mm (9,84”).
- Printing paper roll diameter in exit 250 mm (9,84”).

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

MODEL RP02-1800

6. TECHNICAL DATA:

- 6.1. Installed power: 9,84 kW
- 6.2. Average electrical consumption: 6,70 kWh
- 6.3. Compressed air pressure: 3-8 bar
- 6.4. Mechanic speed: 0.1 ÷ 1,7 m/min
- 6.5. Overall dimensions: width 3.100 mm (122,05"). length 1.240 mm (48,82"). height 1.435 mm (56,50").
- 6.6. Net weight: 1.500 Kg
- 6.7. Machine produced according to CE rules
- 6.8. Customs tariff: 84 51 80 30

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

INNOVATION
SPEED
FLEXIBILITY
PROJECT&DESIGN
INSTALLATION AND ASSISTANCE

 **MONTI ANTONIO®**
STANDARD & CUSTOM HEATING SOLUTIONS
Monti Antonio S.p.A.
Head Office: via dell'Elettronica n°5, 36016 Thiene (VI) Italy
Operation and Administration: via della Fisica n°6, 36016 Thiene (VI) Italy
T. +39 0445 364619 +39 0445 364707 - sales@montiantonio.com
www.montiantonio.com